## FOLLMER DEVELOPMENT, INC.

840 Tourmaline Drive Newbury Park, CA 91320 (805) 498-4531 Fax #: (805) 499-4668

## MATERIAL SAFETY DATA SHEET

Issue Date: 6/10/11

		IDDAG Date: 0/10/1
	SECTION I	
Emergency Telephone Number: 1-800-742-7520	Chemtrec 24 Hour Phone Number: 1-800-424-9300	
Identity: CBI - FOOD RELEASE, NARURALLY LITE, 1	70Z	
Ingredients Name: Water, Soybean Oil, Soy Lecithin, Sorbic Acid, Po	otassium Sorbate and Propellant.	
Other: Aerosol Pan Coating/Food Release Cooking Spray		

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION					
Hazardous Ingredients as defined by OSHA, 29 CFR 1910.1200.					
			ACGIH	OSHA	Other Limits
Chemical Name	Common Name	CAS No.	TLV	PEL_	Recommended
Propane/Isobutane	Propellant	68476-86-8	900 ppm	unknown	
DOT Classification: Aerosols, Flammable gas (each not exceeding 1 liter capacity), UN1950					
SARA reportable quantity 25	5000 lbs.				

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS			
Boiling Point(°F): -5.92°F Aeropres 55 (A-55)	Specific Gravity (H <sub>2</sub> O=1): 0.5498		
Vapor Pressure (mm Hg): 55 ± 5 PSIG@ 70°F	Percent Volatile by Volume(%): 16 - 18%		
Vapor Density (Air=1): 1.8577	Evaporation Rate (nBu0Ac=1): Slower than b-acetate		
Solubility in Water: Negligible	Appearance and Odor: Clear odorless gas		

SECTION IV - FLAMMABILITY AND REACTIVITY				
Flash Point (Method Used):	-131.09°F propellant.	Explosive Limits: LEL: 1.8% UEL: 9.5%		
	625°F concentrate			
Extinguishing Media: Use CO <sub>2</sub> or dry chemical, water may be ineffective				
1 6 6	C 11	tus with a full face piece operated in a positive pressure mode. Water fog Vapors are heavier than air and may travel along the ground to sources of		
Unusual Fire Hazards: Exposure to temperatures over 120°F may cause cans to burst. Reports have been made of ignition from pilot lights, heaters, etcetera after vapors have been moved by ventilating fans. Exploding cans may travel great distances spewing burning materials.				
Stability	Unstable:	Conditions to Avoid: None Known		
	Stable: X			
Incompatibility (Materials to Avoid): Strong oxidizers, heat and ignition sources.				
Hazardous Decomposition/By Products: Oxides of carbon, nitrogen.				
Hazardous	May Occur:	Conditions to Avoid: None Known		
Polymerization	Will Not Occur: X			

All American Aero Foods Pan Coating products are not considered to be or to contain hazardous chemicals based on evaluations made under the Occupational Safety and Health Administrator's Hazard Communication Standard, 29 CFR 1910.1200. As food products that are subject to Federal Food and Drug Administration regulations, each pan coating can contains the required warning statements concerning the safe handling of pressurized containers.

## SECTION V - HEALTH AND SAFETY DATA

Route(s) of Entry: Eye contact, inhalation, skin contact.

Health Hazards (Acute and Chronic): Eye contact can cause pain and slight corneal injury, vapors irritate eyes. Breathing may be mildly anesthetic, narcotic effects may be seen in the 5000-10000 ppm range. Progressively higher levels can cause dizziness, unconsciousness and death. Prolonged or repeated skin contact may cause irritation, defatting.

Sign and Symptoms of Exposure: Eye contact may cause pain, tearing, itching, swelling and/or redness. Inhalation may cause dizziness, and at high levels unconsciousness or death. Prolonged skin contact may result in redness, itching and irritation.

Medical Conditions Generally Aggravated by Exposure: Pre-existing dermatitis conditions may be aggravated by prolonged contact with the product.

Emergency and First Aid Procedures: Eyes: Irrigate with flowing water at least 10 minutes. Hold lids open as it helps prevent scratching and minimize irritation. Seek medical attention as material may become imbedded. Skin: Wash with soap and water. Consult a physician if irritation persists. Ingestion: Do not induce vomiting. Call a physician or poison control center immediately. Inhalation: Remove to fresh air. If not breathing, give mouth to mouth resuscitation. If breathing is difficult give oxygen. Call a physician as excessive exposure may cause irritation to the upper respiratory system.

## SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

Precautions to be Taken in Handling and Storing: Store below 120°F. Avoid direct sources of heat and ignition. Consult local fire marshall and insurance representative for specific storage requirements in your area.

Other Precautions: Do not use deformed or damaged cans. Keep out of reach of children.

Steps to be Taken in Case Material is Released or Spilled: Small spills: Absorb with inert material and dispose in trash. Large spills: Not likely with aerosol cans. Extinguish sources of ignition, ventilate area to remove propellant vapors. Be cautious of low lying areas where vapors will accumulate. Do not enter areas without protective equipment. Do not allow to enter ground water or sewer systems. Absorb with inert material and place in waste disposal drums. Report spill if required by SARA III.

Waste Disposal Method: When disposing of unused containers, the preferred method is to send to a licensed reclaimer or incineration facility capable of handling aerosol cans. Do not puncture or incinerate without the proper equipment as explosions are likely to occur with disastrous effects. In all instances dispose in accordance with federal, state and local guidelines.

SECTION VII - SPECIAL PROTECTION INFORMATION				
Respiratory Protection (Specify Type): If using in areas where the TLV is likely to be exceeded, use a NIOSH/MSA approved respirator.				
Local Exhaust: None required with normal use.	Special: None			
Mechanical (General): Acceptable	Other: None			
one required with normal usage.	Protective Gloves: None required with normal use.  Protective gloves should be worn if prolonged direct contact is anticipated.			
	ion (Specify Type): If using in areas where the TLV is like  Local Exhaust: None required with normal use.  Mechanical (General): Acceptable			

\*N.A. - Not Applicable

\*N.K. - Not Known

The submission of this MSDS may be required by law, but this is not an assertion that the substance is hazardous when used in accordance with proper safety practices and normal handling procedures. Data supplied is for use only in connection with occupational safety and health.