MATERIAL SAFETY DATA SHEET

Section I – Product & Company Identification

Product Name CBI TROPIC BREEZE METERED AIR FRESHENER

Effective Date June 3, 2010

Company Information Cheney Brothers, Inc.

One Cheney Way

Riviera Beach, FL 33404

Company Phone 561-845-4700

Emergency Assistance: 800-424-9300

International 202-483-7616

Section II - Hazardous Ingredients

Emergency Overview CONTENTS UNDER PRESSURE

Aerosol. Pressurized container may explode when exposed to heat or flame.

Harmful if in contact with eyes. Prolonged exposure may cause chronic effects.

OSHA Regulatory Status

Potential Health Effects This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Eves Contact may irritate or burn eyes.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhea. May cause delayed lung damage.

Target Organs Central nervous system. Respiratory system.

Chronic Effects Conjunctiva. May cause central nervous system disorder, (e.g. narcosis involving a loss of

coordination, weakness, fatigue, mental confusion,, and blurred vision) and/or damage..

Signs and symptoms Corneal damage. Narcosis. Conjunctivitis.

Section III - Composition/Information on Ingredients

ComponentsCASPercentAcetone67-64-170-80Propane74-98-610-15n-Butane106-97-810-15Non-hazardous and other components below reportable levels2.5 - 10

Section IV - First Aid Measures

First Aid Procedures

Eye Contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Get medical attention immediately.

Skin Contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical

attention if irritation develops or persists.

Inhalation Call a physician if symptoms develop or persist.

Ingestion Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If

vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If ingestion of a large

amount does occur, seek medical attention.

Note to Physician Symptoms may be delayed.

General Advise If you feel unwell, seek medical advice (show the label where possible).

Section V- Fire And Explosion Data

Flammable Properties Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash

back.

Extinguishing Media

Suitable Extinguishing Media Water fog. Foam. Dry chemical. Carbon dioxide (CO2).

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Protection of Fire Fighters

Protective Equipment and In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing,

Precautions for Fire Fighters	including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.				
	Section VI – Ac	ccidental Release M	easures		
Personal Precautions	Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.				
Methods for Containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable				
Methods for Cleaning Up	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.				
	Section VII –	Handling And Stor	age Procedures		
Handling Storage	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Level 3 Aerosol Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.				
	Section VIII – E	xposure Controls, I	Personal Protection		
Exposure Limits ACGIH					
Components	CAS#	TWA	STEL	Ceiling	
Acetone	67-64-1	500 ppm	750 ppm	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	
n-Butane	106-97-8	1000 ppm	Not established	Not established	
OSHA					
Components	CAS# TWA	STEL	Ceiling		
Acetone	67-64-1	1000 ppm	Not established	Not established	
Propane	74-98-6	1000 ppm	Not established	Not established	
Engineering Controls Personal Protective Equipment	Ensure adequate venti	lation, especially in	confined areas.		
Eye/Face Protection	Wear chemical goggle	26			
Skin Protection	Not normally needed.				
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified				
F			od industrial hygiene and		
	Section IX – Pl	nysical And Chemic	al Data		
Appearance	Compressed liquefied	gas.			
Color	clear				
Odor	fruity				
Physical State	Liquid.				
Form	Aerosol.				
Flammability	31.6624 kJ/g estimate	d			
Flash Back	No				
Pressure	65-75 psig @70°F				
Solubility	Partially				
The state of the s	1560E (104 40C)				

-156°F (-I04.4°C) estimated

68° F (12.8°C) estimated

0.734 estimated

Not applicable

Flash Point

pН

Boiling Point Specific Gravity

\Section X – Reactivity Data

Chemical Stability Risk of ignition. Stable at normal conditions.

Conditions to Avoid Heat, flames and sparks **Hazardous Decomposition Products** May include oxides of nitrogen

Section XI - Toxicological Information

Acute Effects Acute LD50: 25647 mg/kg estimated, Rat, Oral

Acute LD50: 28297 mg/kg estimated, Rat, Dermal Acute LC50: 107 mg/l/4h estimated, Rat, Inhalation

Not expected to be hazardous by OSHA criteria.

Local Effects Contact may irritate or burn eyes.

Chronic Effects Hazardous by OSHA criteria. Repeated absorbtin may cause disorder of central nervous system, liver,

kidneys and blood. Prolonged exposure may cause chronic effects.

Neurological Effects Hazardous by OSHA criteria.

MutagenicityNot expected to be hazardous by OSHA criteria.Reproductive EffectsNot expected to be hazardous by OSHA criteria.TeratogenicityNot expected to be hazardous by OSHA criteria.EpidemiologyNot expected to be hazardous by OSHA criteria

Further information Symptoms may be delayed.

Section XII – Ecological Information

Ecotoxicity LC50 7831 mg/L estimated, Fish, 96.00 Hours.

ELC50 17782 mg/L estimated, Daphnia, 48.00 Hours.

Components of this product have been identified as having potential environmental concerns.

Section XIII - Disposal Considerations

Waste Codes D001: Waste Flammable material with a flash point <140 F

D018: Waste Benzene

Disposal Instructions Consult authorities before disposal. Contents under pressure. Do not puncture incinerate or crush.

Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable

regulations.

Section XIV – Transport Information

Department of Transportation

Basic Shipping Name

Proper Shipping Name Consumer commodity

Hazard Class ORM-D Subsidiary Hazard Class None

Additional Information

Packaging Non Bulk156, 306Packaging Exceptions156, 306Packaging BulkNone

IDMG

Sensitization

Basic Shipping requirements

Proper Shipping Name AEROSOLS, flammable

Hazard Class2.1UN number1950

Additional Information

Items5FLabels required2.1Transport category2

IATA

Basic Shipping requirements

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1





UN number 1950

Section XV - Regulatory Information

US Federal Regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

Yes

chemical

CERCLA (Superfund) reportable quantity

Acetone: 5000,0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard- Yes

Delayed Hazard-no Fire Hazard- Yes Pressure Hazard- Yes Reactivity Hazard-No

Section 302 Extremely

Hazardous substance No

Section 311 Hazardous chemical Yes

Inventor Status

Country(s) or Region	Inventory Name	On Inventory (Yes/No)
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State Regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone 67-64-1 Environmental Hazard

n-Butane 106-97-8 Present Propane 74-98-6 Present

Section XVI - Other Information

HMIS® Ratings Health: I

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in

any process, unless specified in the text.

Issue Date: 12-Nov-2007